

Technological Challenges and Solutions in Hydrothermal Vent Energy Development for Indonesia's Energy Resilience

Fakhriyan Ardyanto¹, Suyono Thamrin², & Rudy Laksmono³

¹²³ Department of Energy Resilience, Faculty of Defense Management, The Republic of Indonesia Defense University, Indonesia

Corresponding Author: fakhriyan.ardyanto@mp.idu.ac.id

Abstract

Indonesia's exceptional geothermal position along the Pacific Ring of Fire presents the nation with an opportunity to develop hydrothermal vent energy as a significant renewable resource, with a potential estimated at 29,000 megawatts. However, despite this promise for energy resilience, formidable technological barriers have prevented the practical implementation of deep-sea thermal systems. This study investigates the primary technological challenges through systematic literature analysis and descriptive research, examining six critical domains: material durability and corrosion resistance, subsea engineering design and equipment reliability, thermal energy extraction and efficiency, infrastructure deployment and maintenance, ecosystem protection, and regulatory frameworks. By synthesizing findings from academic research, government reports, and industry expertise, the research reveals both substantial obstacles and emerging solutions. At the same time, challenges are significant, encompassing material degradation, system reliability, thermodynamic efficiency, and deep-sea deployment. Practical pathways forward exist through the use of advanced materials, innovative engineering, rigorous testing, and adaptive environmental management. The study proposes a phased implementation strategy that progresses from research and pilot demonstrations through technology refinement to commercial deployment. This work offers essential guidance for policymakers, engineers, and energy security specialists seeking to harness Indonesia's hydrothermal potential while maintaining environmental sustainability, operational reliability, and advancing national energy resilience.

Keywords: Technological challenges, Hydrothermal vents, Energy resilience, Energy technology, Renewable energy



INTRODUCTION

Renewable energy has become of key focus in the global effort to reduce dependence on fossil fuels and address climate change (IEA, 2023). Among various renewable energy sources, hydrothermal vents hold significant potential, particularly for countries with high geothermal activity, such as Indonesia. Hydrothermal vents are openings on the ocean floor that release hot water and minerals from within the Earth to the sea surface, creating a unique ecosystem rich in life. As of 2009, more than 250 hydrothermal vents had been visually documented, and this number was later confirmed using advanced detection methods in the deep-sea column (NOAA Ocean Exploration, 2013).

Indonesia, located in the Pacific Ring of Fire, has over 400 volcanoes and is one of the countries with the most extensive geothermal potential in the world. According to data from the Ministry of Energy and Mineral Resources (ESDM), Indonesia's geothermal energy potential is estimated to reach 29,000 megawatts (MW), with hydrothermal vents representing an untapped frontier for energy generation (Ministry of Energy and Mineral Resources, 2020). However, despite this tremendous potential, the development of hydrothermal vent energy technology has faced significant technological barriers that must be overcome to realize the full contribution of this renewable energy source to national energy resilience.

While the energy potential is evident, the critical gap lies in understanding and addressing the technical challenges inherent in harnessing this resource. This research aims to identify the significant technological challenges in hydrothermal vent energy development and propose feasible solutions that align with Indonesia's energy resilience objectives.

The research question is: What are the primary technological challenges in developing hydrothermal vent energy, and what solutions can enable Indonesia to effectively implement this technology while maintaining environmental sustainability and operational reliability?

METHOD

Our research employs a mixed-methodology approach, centered on systematic literature analysis and interpretive description, to investigate the development of hydrothermal vent energy within Indonesia's energy context. The investigation sources information from multiple authoritative repositories, including academic journals, scholarly monographs, research reports, and official governmental publications. The initial phase involves strategic identification, careful examination, and analytical integration of existing literature addressing hydrothermal vent phenomena and Indonesia's renewable energy landscape.

This phase prioritizes the incorporation of recent, validated information from recognized



academic and institutional sources. Subsequent data gathering incorporates materials from established scholarly journals, authoritative government agencies, and recognized industry bodies, with concentrated focus on geothermal capacity assessments, hydrothermal vent location and distribution data, and the policy environment governing renewable energy development across Indonesia. Information synthesis proceeds through the structured organization of collected materials, systematic evaluation of source reliability and methodological soundness, cross-disciplinary information integration, and interpretive analysis that connects findings to the central research questions (Moleong, 2007). This approach produces a nuanced examination of both the opportunities and technical obstacles inherent in hydrothermal vent energy development, culminating in recommendations grounded in empirical evidence.

RESULTS AND DISCUSSION

Hydrothermal Vents: Resource Characteristics and Energy Potential

A hydrothermal vent is a natural phenomenon occurring when seawater seeps through cracks in the oceanic crust, particularly around subduction zones and mid-ocean ridges. Cold seawater infiltrates the Earth's crust, becomes heated by hot magma, and rises back to the surface, carrying dissolved minerals such as copper, zinc, iron, lead, sulfur, and silica (Kelley, 2001). Water temperatures at hydrothermal vents can exceed 340°C (704°F), yet remain in a liquid state due to extreme pressure at ocean depths (Omran et al., 2020)

Two primary types of hydrothermal vents exist based on chemical composition and fluid characteristics:

Table 1. Comparison of Black Smoker and White Smoker Characteristics (Ardyanto, 2025)

Characteristic	Black Smokers	White Smokers
Primary Minerals	Sulfide particles (dark)	Sulfide minerals (white)
Temperature Range	>340°C	250-300°C
Vent Depth	2-8 km in oceanic crust	Variable, shallower zones
Flow Rate	Faster	Slower
Chimney Structure	Larger	Smaller
Mineral Composition	Iron, zinc sulfides	Anhydrite-rich



Black Smokers form in deep ocean environments through hydrothermal circulation. White Smokers result from the chemical precipitation of minerals when hydrothermal fluids mix with seawater before exiting the vent, creating white-colored mineral deposits (Omran et al., 2020).

Energy Potential for Indonesia

The heat energy contained within hydrothermal vent systems represents a vast untapped resource. The continuous thermal gradient between vent fluids (250-400°C) and ambient seawater (2-4°C) creates theoretical energy conversion potential through thermoelectric and thermal conversion technologies. For Indonesia specifically, the geographic distribution of active hydrothermal vents along the Sunda Arc and surrounding regions aligns with the nation's volcanic activity, providing strategic locations for energy extraction infrastructure.

Technological Challenges in Hydrothermal Vent Energy Development

Material Science and Corrosion Challenges

The extreme environment of hydrothermal vent systems presents unprecedented challenges to material durability and longevity. At depths of 1,500 to 2,000 meters, subsea equipment encounters aggressive corrosive conditions characterized by high salinity, aggressive dissolved minerals, sulfide particles, and thermal fluctuations. The combination of these factors creates an environment that rapidly degrades conventional materials used in offshore engineering. Steel components, which are standard in marine infrastructure, suffer accelerated corrosion due to the electrochemical reactions promoted by the mineral-rich, acidic fluids expelled from hydrothermal vents. Titanium and its alloys, while superior to steel in corrosion resistance, remain prohibitively expensive for large-scale deployment and still face degradation from concentrated sulfide solutions present in hydrothermal fluids (Stroud, 2019).

The challenge of material compatibility extends beyond simple corrosion to include stress-corrosion cracking, hydrogen embrittlement, and biofouling that can compromise structural integrity over time. The highly acidic nature of some hydrothermal vent fluids, combined with the presence of reactive hydrogen sulfide gas, creates conditions that accelerate material degradation through multiple simultaneous mechanisms. Furthermore, thermal cycling as fluids flow through the system creates mechanical stresses in materials, leading to fatigue and eventual failure. Advanced composite materials and newly developed high-performance alloys hold promise for addressing these challenges, although their development and certification for subsea use require extensive research and testing. Protective coating technologies, such as





advanced ceramic or polymer-based coatings that can self-heal when damaged, represent an innovative approach to extending component lifetime. Additionally, cathodic protection systems specifically designed for the unique electrochemistry of hydrothermal vent environments can be implemented to reduce corrosion rates.

Equipment Reliability and Engineering Design

The translation of hydrothermal vent energy potential into reliable, operational power generation systems requires engineering solutions that function reliably in one of Earth's most hostile environments. Equipment must operate at temperatures exceeding 300°C while simultaneously withstanding pressures of 150+ atmospheres and remaining submerged in corrosive seawater. Traditional offshore equipment, developed for conventional oil and gas operations, is fundamentally inadequate for these conditions. The heat exchangers that transfer thermal energy from hydrothermal fluids to working fluids must maintain efficiency while resisting both thermal and chemical stresses. Similarly, pumps and piping systems must reliably circulate fluids without cavitation, thermal shock, or mechanical failure over extended periods without maintenance intervention.

The design of subsea turbines presents engineering challenges, as these devices must convert thermal or kinetic energy into mechanical rotation under extreme operational constraints. Current deep-sea turbine designs have been optimized primarily for hydrokinetic applications with relatively benign thermal conditions, making them unsuitable for direct application in hydrothermal environments (Chen et al., 2021). Control systems that regulate power output, manage thermal cycles, and prevent equipment damage must operate reliably in total darkness at crushing depths where remote intervention is effectively impossible. Redundancy and fail-safe mechanisms become critical design considerations; however, they introduce significant complexity and increase the cost of the system architecture.

Innovative engineering approaches include modular design philosophies that enable in-situ component replacement without requiring an entire system shutdown, the development of autonomous control systems with advanced sensor packages, and the creation of standardized subsea component interfaces that facilitate rapid deployment and maintenance operations.

Thermal Energy Extraction and Conversion Efficiency

The efficient capture and conversion of hydrothermal vent energy into usable electricity represents a fundamental technological challenge that directly determines economic viability. Hydrothermal fluids contain tremendous thermal energy; however, traditional heat-to-





electricity conversion systems, such as Rankine cycles or Brayton cycles, operate at thermodynamic efficiencies that are substantially reduced in the deep-sea environment, where cooling fluids are limited. The temperature differential between hydrothermal fluid and the surrounding ocean water is significant (typically 250-340°C for vent fluid versus 2-4°C for deep ocean water); yet, accessing this differential requires efficient heat transfer mechanisms that can function reliably in hostile conditions.

Binary cycle systems, which utilize intermediate working fluids with lower boiling points than water to enhance efficiency, encounter challenges in maintaining optimal operating parameters when both the heat source and cooling medium are subject to fluctuations. The deep-sea location of hydrothermal vents means that cooling fluid (if ocean water is used directly) contains dissolved minerals that can precipitate and foul heat exchanger surfaces, reducing efficiency over time. Alternatively, circulating dedicated cooling systems adds significant complexity and parasitic power requirements that reduce net energy output. Multiphase flow phenomena within the system, where steam, liquid water, and mineral-laden streams flow simultaneously through different sections, create thermodynamic inefficiencies and potential equipment damage (Rane, 2020). Addressing these challenges requires the development of advanced materials for heat exchangers that resist fouling, the creation of innovative cycle designs explicitly tailored to the hydrothermal environment, the implementation of real-time monitoring systems that optimize operating parameters, and the potential use of nanofluids or other advanced working fluids that enhance heat transfer while maintaining stability.

Subsea Infrastructure and Deployment Technology

Deploying and maintaining complex mechanical systems on the deep seafloor presents engineering challenges of unprecedented magnitude. The construction of capture domes, heat exchangers, turbines, generators, piping systems, and supporting infrastructure at depths of 1,500-2,000 meters requires specialized vessels, remotely operated vehicles (ROVs), and installation techniques that are extraordinarily expensive and technically demanding. The irregular topography of hydrothermal vent fields, characterized by steep slopes and unstable seafloor conditions, complicates site selection and foundation design. Hydrothermal vent systems are geologically active environments where fluid chemistry, temperature, and flow rates can change unpredictably, requiring adaptive infrastructure design that can accommodate such variations. Cable and conduit routing from the deep seafloor to surface collection platforms or subsea power transmission nodes must navigate complex bathymetry while avoiding damage from bottom currents, trawling activities, and geological movements. Submarine power





transmission cables capable of operating at the voltages and distances required for practical power export remain a significant engineering challenge, with only limited deployments in experimental settings (Clare, 2023).

The lack of established infrastructure and supply chains for deep-sea energy systems means that most components must be custom-designed and fabricated, resulting in dramatically increased costs and timelines. Additionally, the need for routine maintenance and component replacement without bringing the entire system to the surface necessitates the development of innovative tooling, docking systems, and specialized maintenance procedures. Solutions include the development of standardized, modular subsea architecture that facilitates component access and replacement, the creation of advanced remotely operated vehicles specifically designed for maintenance in hydrothermal environments, the establishment of staging facilities in nearby coastal areas for equipment refurbishment, and the investigation of autonomous subsea robotic systems that can conduct repairs and maintenance autonomously.

Environmental and Biological Impact Assessment

While hydrothermal vent energy represents a renewable alternative to fossil fuels, implementing large-scale energy extraction from these systems raises important questions about environmental sustainability and ecosystem preservation. Hydrothermal vents support unique chemosynthetic ecosystems that exist nowhere else on Earth, with specialized organisms adapted to extreme temperatures, pressures, and chemical compositions. These environments host bacteria, crustaceans, molluscs, and other organisms in complex food webs driven by chemical energy rather than photosynthesis. Large-scale energy extraction could fundamentally alter these unique ecosystems by changing fluid flow rates, temperature distributions, and chemical compositions of vent emissions.

The capture of hydrothermal fluid for energy extraction would reduce the quantity of minerals and chemical compounds reaching the surrounding water, potentially disrupting the nutrient cycles that support vent ecosystems. Similarly, thermal changes from energy extraction could reduce the temperature gradients that create habitat diversity within vent fields. The installation of large physical structures would directly displace organisms and modify habitat structure. Remote monitoring and assessment of ecosystem impacts poses significant challenges given the depth and inaccessibility of vent systems. Regulatory frameworks and environmental impact assessment methodologies developed for shallow-water activities prove inadequate for deep-sea hydrothermal systems, where scientific understanding remains incomplete. Addressing environmental concerns requires implementation of comprehensive baseline





biological surveys before energy extraction begins, development of monitoring protocols to track ecosystem changes during and after energy extraction, design of extraction systems that minimize fluid diversion and temperature modification, establishment of marine protected areas around sensitive vent fields, and commitment to research funding for ongoing ecosystem assessment and adaptive management protocols (Chen et al., 2024).

Regulatory and Jurisdictional Framework

The legal and regulatory landscape governing hydrothermal vent energy development remains substantially underdeveloped compared to established offshore energy sectors. Hydrothermal vents occur within Indonesia's extended continental shelf and exclusive economic zone, establishing national jurisdiction; however, international law regarding deep-sea resource extraction and environmental protection remains unclear. The United Nations Convention on the Law of the Sea (UNCLOS) provides the foundation for maritime jurisdiction. However, specific regulations governing the extraction of subsea energy from hydrothermal vents have not been comprehensively developed. Indonesia's existing maritime legislation addresses oil and gas development, fishing, and shipping, but lacks specific provisions for novel deep-sea energy technologies.

Environmental regulations require environmental impact assessments and permits; however, the extraordinary environmental sensitivity of hydrothermal ecosystems and the incomplete scientific understanding of these systems create challenges in establishing clear permit criteria and environmental standards. International precedents and best practices for hydrothermal vent exploitation remain limited, as no large-scale commercial operations currently exist. The intellectual property frameworks for novel subsea energy technologies remain uncertain, complicating private investment and technology transfer. Coordination between multiple Indonesian government agencies, including the Ministry of Marine Affairs and Fisheries, the Ministry of Energy and Mineral Resources, and various regional authorities, requires the establishment of clear institutional responsibilities and decision-making procedures. Additionally, consultation with indigenous communities and maritime stakeholders who depend on marine resources must be conducted in a transparent manner (Asimakopoulou, 2019).

Developing a comprehensive regulatory framework requires convening expert commissions to develop clear technical standards, establishing of environmental protection guidelines specifically for deep-sea hydrothermal systems, creating of licensing and permitting procedures adapted to the unique characteristics of hydrothermal vent energy, engaging with



international bodies to harmonize standards with global best practices, and committing to transparent stakeholder consultation processes.

Integration of Solutions: A Development Pathway for Indonesia

Phased Implementation Strategy

Successful hydrothermal vent energy development requires strategic sequencing:

Phase 1: Research and Pilot Demonstration (Years 1-5)

- High-resolution mapping and characterization of Indonesian hydrothermal vent sites
- Material testing programs in representative vent environments
- Small-scale prototype energy extraction system deployment and testing
- Comprehensive environmental baseline and impact studies
- Regulatory framework development and international engagement

Phase 2: Technology Refinement and Scale-Up (Years 5-10)

- Advancement of materials and corrosion resistance solutions
- Demonstration of reliable thermal extraction and conversion systems
- Development of integrated subsea infrastructure and monitoring capability
- Commercial viability assessment and economic modelling
- Workforce training and capacity building in marine energy technology

Phase 3: Commercial Deployment (Years 10+)

- Installation of commercial-scale energy extraction systems at proven vent sites
- Grid integration and power transmission infrastructure development
- Full-scale environmental monitoring and adaptive management
- Expansion to multiple vent sites based on demonstrated success
- Contribution to national energy resilience and decarbonization targets

Synergies with Existing Indonesian Energy Infrastructure

Hydrothermal vent development complements Indonesia's renewable energy portfolio:

- Baseload renewable energy source complementing variable solar and wind capacity
- Geographic proximity to existing deep-water oil/gas infrastructure enables technology adaptation
- Potential for hybrid systems combining geothermal (terrestrial) and hydrothermal (marine) resources
- Opportunity to establish Indonesia as a regional leader in marine energy technology innovation
- Enhanced energy security through geographic diversification of energy sources



CONCLUSION

Hydrothermal vent energy development presents a technically challenging but potentially transformative pathway for Indonesia's energy resilience. The primary technological obstacles, such as material corrosion, equipment reliability, thermal conversion efficiency, subsea infrastructure, environmental protection, and regulatory frameworks, are substantial yet addressable through targeted research and development efforts.

Solutions exist or are emerging across all identified challenge domains. Success requires:

1. **Sustained investment** in fundamental research on materials, thermodynamics, and subsea systems
2. **Interdisciplinary collaboration** among materials scientists, engineers, marine biologists, and policy experts
3. **International engagement** to establish supportive regulatory frameworks and knowledge-sharing mechanisms
4. **Strategic partnerships** leveraging existing offshore industry expertise and infrastructure
5. **Long-term commitment**, recognizing that transformation to mature technology requires 10-15 year timescales

The convergence of Indonesia's exceptional geological endowment (located in the Ring of Fire), advancing ocean technology capabilities, and urgent national energy security imperatives creates a compelling case for prioritizing hydrothermal vent energy development. While technological challenges are real and significant, they are not insurmountable. With focused effort, Indonesia can help pioneer the emergence of hydrothermal vent energy as a significant contributor to sustainable and resilient energy systems.

The transition from scientific curiosity to operational energy source demands commitment to solving technological challenges systematically. Indonesia has the opportunity to lead this emerging sector while strengthening national energy independence.

REFERENCE

- Ardyanto, F., Thamrin, S., & Laksmono, R. (2025). Potential of Renewable Energy from Hydrothermal Vents for National Energy Resilience in Indonesia. *International Journal of Renewable Energy Resources*. 15(2025) 1–7.
- Asimakopoulou, E. & Mohammed, E. (2019). *Marine genetic resources in areas beyond national jurisdiction: a 'common heritage of mankind'*. Available at <https://www.iied.org/17498iied>.
- Chen, C., Hookabe, N., Hashimoto, R., Shimooka, S., Shiraki, S., Uyeno, D., & Kawagucci, S. (2024).





- Faunal Composition of the Sumisu Caldera Hydrothermal Vent Field as a Key Baseline for Conservation in Light of Deep-Sea Mining. *Aquatic Conserv: Mar Freshw Ecosyst*, 34: e70009. <https://doi.org/10.1002/aqc.70009>
- Chen, Y., Liu, Y., Zhang, L., & Yang, X. (2021). Three-Dimensional Performance Analysis of a Radial-Inflow Turbine for Ocean Thermal Energy Conversion System. *Journal of Marine Science and Engineering*, 9(3), 287. <https://doi.org/10.3390/jmse9030287>
- Clare, M.A., Lichtschlag, A., Paradis, S. *et al.* (2023). Assessing the impact of the global subsea telecommunications network on sedimentary organic carbon stocks. *Nat Commun* 14, 2080 (2023). <https://doi.org/10.1038/s41467-023-37854-6>
- IEA (2023), *World Energy Outlook 2023*, IEA, Paris <https://www.iea.org/reports/world-energy-outlook-2023>, Licence: CC BY 4.0 (report); CC BY NC SA 4.0 (Annex A)
- Kelley, D.S. (2001). Black Smokers: Incubators on the Seafloor. In: *Earth Inside and Out*, (ed. E. Mathez) American Museum of Natural History, pp. 184–189, The New Press, New York.
- Kelley, D.S., *et al.* (2002). A new perspective on the origin of hydrothermal vents and their ecosystems: Insights from molecular biology and geology. *Science*, 295(5558), 1965–1969.
- Ministry of Energy and Mineral Resources, Republic of Indonesia. (2020). *Indonesia's Renewable Energy Potential and Development Strategy*. Jakarta: ESDM Publications.
- Moleong, L. J. (2007). Metodologi penelitian kualitatif edisi revisi. In Bandung: PT Remaja Rosdakarya (Vol.103).
- NOAA Office of Ocean Exploration and Research (2010). *Mission Plan: Background Information: INDEX 2010: "Indonesia-USA Deep-Sea Exploration of the Sangihe Talaud Region"*. NOAA Office of Ocean Exploration and Research. Retrieved June 11, 2025, from <https://oceanexplorer.noaa.gov/oceanos/explorations/10index/background/plan/plan.html>
- NOAA. (2013). A Hydrothermal Vent Forms when Seawater Meets Hot Magma, Retrieved November 29, 2024, from <http://oceanservice.noaa.gov/facts/vents.html>.
- Omran, A. & Pasek, M. (2020). A Constructive Way to Think about Different Hydrothermal Environments for the Origins of Life. *Life*. 10. 36. 10.3390/life10040036
- Rane, S., He, L. (2020). CFD analysis of flashing flow in a two-phase geothermal turbine design. *Journal of Computational Design and Engineering*. 7(2)-4, 238–250,
- Stroud, A., & Ertas, A. (2019). Complex Multi-System Integration Problems Associated with Titanium Metalworking and Manufacture: System of Systems Approach—Part I. *Metals*, 9(4), 424. <https://doi.org/10.3390/met9040424>

